



M.D. STETSON

UNIVERSAL FLOOR FINISH

Using state-of-the-art thermo-fusion technology to combine several polymers, we have formed the strongest bond possible in a removable floor finish. Stronger than finishes that use metal crosslink bonds, Universal is extremely durable, resistant to scratching and black-heel marks, and highly responsive to buffing at all speeds. This finish performs as both a sealer and finish on almost any hard floor surface including VCT, terrazzo, rubber, linoleum, marmoleum, and concrete. Only damp mopping or autoscrubbing with a neutral cleaner, periodic mopping with a restorer, and buffing is necessary to continually restore its “wet look” gloss. Routine maintenance and a periodic scrub and recoat is all that is needed for up to three years.

DIRECTIONS FOR USE:

- 1. Preparation:** Strip or scrub floor removing the desired amount of finish using a Stetson stripper or Winterclean 365 for scrubbing. Thoroughly rinse the floor using Winterclean 365. Application of **Universal** should be on completely clean floor.
- 2. Optional:** If surface is in worn condition or porous, use **Universal** or a Stetson sealer first to seal the floor.
- 3. Application:** Do not dilute **Universal**. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.
 - Always wait 24 hours before buffing newly applied finish.
 - Never use a stripper or a high pH cleaner for routine maintenance.

Maintenance:

1. Sweep or dry mop floors on a daily basis.
2. Damp mop or autoscrub with a Stetson neutral floor cleaner or a germicidal cleaner daily. Substitute Winterclean in the winter to remove de-icing salt residues.
3. If a high speed buffing program is used, damp mop or autoscrub with one of Stetson’s premium finish restorers prior to buffing. The result will be a sensational “wet look” gloss, increased slip-resistance, and an extended life for the finish.
4. Worn or soiled areas can be recoated with 1 or 2 coats of **Universal** as needed. Prior to application, scrub the floor with Winterclean using an auto-scrubber or floor machine and the appropriate floor machine pad.

COVERAGE: 2000-3000 square feet, depending on the method of application and the porosity of the floor.

SPECIFICATIONS:

Solids	18-25%
Weight/gallon	8.7 lbs/gal.
pH	7.8-8.2
Viscosity	100 cps
Surfactant	Non-APE
Heat stability	Excellent
Freeze-Thaw stability	passes 3 cycles
Appearance.....	milky white

This product does not contain hazardous ingredients as defined in OSHA 29 CFR 1910.1200. Contains Right-To-Know chemical 2-(2-Ethoxyethoxy)ethanol (CAS #111-90-0).

Refer to the Safety Data Sheet (SDS) for detailed safety, health and environmental information.



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

Disposal: Surfactants biodegradable. Diluted product may be flushed down sewer. Check with local water treatment plant. Recycling container recommended.

Disposición: Surfactants biodegradable. El producto diluido puede ser limpiado abajo alcantarilla. Verifique con planta local de tratamiento de agua. El reciclaje recomendó para el contenedor.

Personal Protection: Protective gloves and safety eye-wear recommended.

Protección Personal: Guantes de protección y gafas de seguridad recomendadas.

Please refer to Stetson’s “Catch the Training” Strip & Refinish, Daily Floorcare or Scrub & Recoat training guides for detailed instructions.

PACKAGING:

Available in 1 gallon jugs, 5 gallon plastic pails, and 55 gallon drums.



FLOOR COATING AND FINISHING MATERIALS AS TO SLIP RESISTANCE ONLY. 3NRJ

December 2017