

110 Maintainer TECHNICAL DATA

MAINTAINER is a high or low speed maintainer for acrylic and acrylic/urethane floor finishes. It is used as a mop on product. Maintainer not only gives a high gloss and wet look, it is also a cleaner. Maintainer may be used in automatic scrubbers or may be used with a low or high speed machine when top scrubbing the floor.

Increases slip resistance. Economical to use. Restores gloss and appearance without finish buildup. Does not soften finish surface. Burnishes out quickly for productivity.

EASY TO USE (Dilute with cold water)

- Dispense automatically with the Product Central Dispensers.
- Simply damp mop the floor using Maintainer.
- Let the floor dry.
- Buff/burnish to a remarkable gloss.
- Maintainer can also be used in a spray bottle for light spray buffing and the removal of stubborn black marks.

Recycling container recommended. Dispose of unused concentrate in accordance with local, state, and federal regulations. Recomienda contenedor de reciclaje. Deshágase de concentrado no utilizado de acuerdo con las ordenanzas locales, estatales y federales.

| SPECIFICATIONS | | |
|--------------------------------|--------------------------------|--------------|
| Dilution half-gallon cartridge | Hi-Flow | 1:300 |
| | Lo-Flow | |
| Dilution 3 liter cartridge | Hi-Flow | 1:300 |
| | Lo-Flow | 1:64 |
| Yield half-gallon cartridge | Hi-Flow | 150 gallons |
| | Lo-Flow | |
| Yield 3 liter cartridge | Hi-Flow | 237 gallons |
| | Lo-Flow | 202 quarts |
| pH as supplied | 2.32-3.45 | |
| pH at dilution | 1:300 4.5-4.8 | 1:64 6.8-7.0 |
| Color | Blue | |
| Odor | Peppermint | |
| Weight per gallon | 9.80 lbs. | |
| Packaging | ½ gallon and 3 liter cartridge | |
| Shelf Life | 2 years unopened | |



Green Certification Statement: This product meets Green Seal™ Standard GS-53 based on effective performance, concentration of product, minimized/recycled packaging, and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

Personal Protection: Neoprene or nitrile gloves. Splash proof safety goggles with side shields.

Protección Personal: Guantes de neopreno o nitrilo. Gafas de seguridad a prueba de salpicaduras con protectores laterales.

The consequences of improper use or improper dilution are residue buildup or reduced effectiveness, as well as an increased risk of adverse health effects.

Ingredients: Water, Cross-linked Polyethylene Glycol, Nonionic Surfactant Blend, C9-11 Pareth-8, PEG-180, Glycolic Acid, Methyl Salicylate, Fluorosurfactant, Dye.

INTEGRATED SYSTEM

Use the Product Central chemical cartridges with the

- Express Wall Mount Dispenser
- Express Portable Dispenser
- Express Foaming Gun

User Friendly

- Simply choose the appropriate chemical.
- Insert the cartridge into the dispenser.
- Select the spray bottle fill button or the bulk fill button.
- Fill spray bottles, buckets, machines, etc.
- The dispenser automatically dilutes the product.

Built-in Features

- Each cartridge comes with its own dilution control mechanism.
- A flow reduction washer keeps pressure constant, assuring accurate dilution.
- Air gap technology protects the water supply.

Smart Packaging

- · Color and number coded labels
- Labels have icons to show proper usage



04/09/2018

