



PRODUCT DATA SHEET

IMPACT LOW ODOR STRIPPER

Impact is a concentrated re-emulsifying floor stripper free of ammonia, butyl solvents and other irritating chemical odors. It removes all acrylic cross-linked and urethane fortified floor finishes. Do not use on painted surfaces. Do not use on linoleum, uncoated rubber or wood flooring.

DIRECTIONS FOR USE:

Use with tepid or warm water. If available, hot water will help soften the finish and hasten the removal of the finish with Impact.

Floor Finish Stripping

1. Clear area of obstacles then dust mop.
2. Remove gum and debris with scraper.
3. Mix 1 gallon of Impact Low Odor Stripper to 5 gallons of water.
 - ½ GAL:5 GAL for 1-3 coats
 - 1 GAL:4 GAL for 4-6 coats
 - 1 GAL:3 GAL for 7+ coats
4. Spread diluted stripper solution liberally over the baseboards and edges surface with a mop or applicator. Allow stripper application to soak for 10-15 minutes. Do not allow solution to dry.
5. Scrub all baseboards and edges using an edge stripping tool such as a 3M Doodlebug equipped with a strip pad.
6. Spread diluted stripper solution liberally over a workable floor surface with a mop or applicator. Allow stripper application to soak for 10-15 minutes. Do not allow solution residue to dry on the floor.
7. Evenly scrub the floor in both directions with a floor machine equipped with a stripping pad. Pick up loosened finish with a wet vac or autoscrubber.
8. Thoroughly rinse and final rinse the floor with Winterclean 365.
9. Allow floor to dry completely, before applying a Stetson floor finish.

10. Apply 4-6 medium coats of floor finish using a clean microfiber pad, finish mop or applicator. Wait at least 30 minutes between coats. On highly humid days extend dry times and reduce the number of coats applied per day.

Heavy Duty Cleaning

1. Dilute Impact 2-32 ounces per gallon of water. Uses include: cleaning kitchen floors, pen and mark removal, industrial equipment and other heavy soils.

Please refer to Next-Gen's "Catch the Training" Strip & Refinish training guide for detailed instructions.

SPECIFICATIONS

Dilution Ratio Stripping	1:3 to 1:10 with water
Density	8.34 lbs./gal.
Alkali Residue	None
pH (ASTM E70)	>12.5
End Use Coverage	1,000 – 2,000 ft.
Freeze Thaw Stability (ASTM D3209)	Passes
Color	Green
Fragrance added	None

Refer to the Safety Data Sheet (SDS) for detailed safety, health and environmental information.

PACKAGING

Available in 1 gallon jugs, 5 gallon pails, and 55 gallon drums.

December 2023



**11 Norfolk Street
Mansfield, MA 02048
877-4-JANSAN
www.nextgensupply.com**

Next-Gen Supply Group is part of Envoy Solutions company, a specialized distributor and solution provider in jan-san, foodservice, packaging, and marketing execution.