



PRODUCT DATA SHEET

ROYAL GLO FLOOR FINISH

Top of the line high-solid thermoplastic polymer blend fortified with urethane that produces a floor finish highly responsive to high speed buffing, including propane machines. Royal Glo dries to a hard clear film, remarkably resistant to scuffing and black heel marking. Royal Glo is easy to-apply and maintain and will give exceptional protection, slip-resistance, and a brilliant shine. Royal Glo produces a three dimensional coating that responds to dry burnishing or further enhanced at any RPM when using a Stetson maintainer or restorer. A floor maintenance program encompassing a routine buffing operation will improve scuff, black-heel marking, and slip-resistance and extend the life of the finish while giving a brilliant gloss.

DIRECTIONS FOR USE:

1. Preparation: Strip or scrub floor removing the desired amount of finish using a stripper or Winterclean 365 for scrubbing. Thoroughly rinse the floor using Winterclean 365. Application of Royal Glo should be on completely clean floor.
2. Optional: If surface is in worn condition or porous, use Royal Glo or a sealer first to seal the floor.
3. Application: Do not dilute Royal Glo. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.
 - Always wait 24 hours before buffing newly applied finish.
 - Never use a stripper or a high pH cleaner for routine maintenance.

COVERAGE:

1500-3000 square feet, depending on the method of application and the porosity of the floor.

Refer to the Safety Data Sheet (SDS) for detailed safety, health and environmental information.

Maintenance:

1. Sweep or dry mop floors on a daily basis.
2. Damp mop or autoscrub daily with Winterclean 365 neutral cleaner or a germicidal cleaner. To remove de-icing salt residues in the winter use Winterclean 365.
3. If a high speed buffing program is used, damp mop or autoscrub with a finish restorer prior to buffing. The result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.
4. Worn or soiled areas can be recoated with 1 or 2 coats of Royal Glo as needed. Prior to application, scrub the floor with Winterclean 365 using an autoscrubber or floor machine and the appropriate floor machine pad.


SPECIFICATIONS:

Appearance	White emulsion
Pounds per gallon	8.60 + .05
Viscosity (Brookfield).....	2.65 + 0.15 cps
Gloss	Excellent
Levelling	Excellent
Crazing	None
Hazing.....	None
Water spot resistance	
1 hour	Very good
24 hours.....	Excellent

PACKAGING:

Available in 1 gallon jugs (4/case), 5 gallon pails, and 55 gallon drums.

February 2024



11 Norfolk Street
Mansfield, MA 02048
877-4-JANSAN
www.nextgensupply.com

Next-Gen Supply Group is part of Envoy Solutions company, a specialized distributor and solution provider in jan-san, foodservice, packaging, and marketing execution.