



# PRODUCT DATA SHEET

## UNIVERSAL FLOOR FINISH

Universal is a zinc-free, APE-free, styrene-acrylic, floor finish with urethane that yields high initial gloss without needing to be buffed, excellent recoat properties for faster application, and outstanding durability. Complies with the stringent requirements put forth by some of today's leading environmental certification agencies. Ideal for areas not maintained on a regular basis. Universal provides an excellent balance of water and detergent resistance while leaving its ease of removability intact; with high off-the-mop gloss, excellent leveling, low mop drag, and outstanding durability. Contains no intentional PFAS.

### DIRECTIONS FOR USE:

- Preparation:** Strip or scrub floor removing the desired amount of finish using a stripper or Winterclean 365 for scrubbing. Thoroughly rinse the floor using Winterclean 365. Application of Universal should be on completely clean floor.
- Optional:** If surface is in worn condition or porous, use Universal or a sealer first to seal the floor.
- Application:** Do not dilute Universal. Apply with a clean finish mop, microfiber pad or applicator, spreading evenly. Apply medium coats. If finish is to be maintained with a high speed buffing program, a base film of 4 to 6 coats of finish is recommended. Allow each coat to dry before applying the next coat. Application should not exceed more than 4 coats of finish in one day. Dry time will range from 20-45 minutes per coat depending on atmospheric conditions. On highly humid days extend dry times and reduce the number of coats applied per day.
  - Always wait 24 hours before buffing newly applied finish.
  - Never use a stripper or a high pH cleaner for routine maintenance.

### COVERAGE:

2000-3000 square feet, depending on the method of application and the porosity of the floor.



### Maintenance:

- Sweep or dry mop floors on a daily basis.
- Damp mop or autoscrub with a neutral floor cleaner or a germicidal cleaner daily. Substitute Winterclean 365 in the winter to remove de-icing salt residues.
- If a high speed buffing program is used, damp mop or autoscrub with a premium finish restorers prior to buffing. The result will be a sensational "wet look" gloss, increased slip-resistance, and an extended life for the finish.
- Worn or soiled areas can be recoated with 1 or 2 coats of Universal as needed. Prior to application, scrub the floor with Winterclean 365 using an autoscrubber or floor machine and the appropriate floor machine pad.

### SPECIFICATIONS:

Weight/gallon.....	8.7 lbs/gal.
pH .....	7.8-8.2
Viscosity .....	< 300 cps
Surfactant .....	Non-APE
Heat stability.....	Excellent
Freeze-Thaw stability.....	passes 3 cycles
Appearance .....	milky white

**Refer to the Safety Data Sheet (SDS) for detailed safety, health and environmental information.**

### PACKAGING:

Available in 1 gallon jugs (4/case), 5 gallon pails, and 55 gallon drums.

March 2026



11 Norfolk Street • Mansfield, MA 02048  
877-4-JANSAN • www.nextgensupply.com  
BradyPLUS Now proudly part of BradyPLUS  
BradyPLUS.com